



TU - L2

LUBRICATOR
LUBRIFICATORE

Attachment / Accessori

L-type bracket (TU-BC2L)
Staffa a L (TU-BC2L)

TECHNICAL FEATURES / CARATTERISTICHE TECNICHE

Port size / Taglia	G 1/4"
Fluid / Fluido	Air / Air
Max. operating pressure Range massimo di pressione	10 Bar
Proof pressure Pressione di scoppio	15 Bar
Ambient temperature Temperatura ambiente	- 5 ~ +60°C (no freezing - no congelamento)
Lubricating oil capacity Capacità tazza olio	20 cc (P), 35 cc (L)
Min. flow for oil drip Flusso minimo gocciolamento olio	50 L/min
Recommended lubricating oil Olio di lubrificazione consigliato	ISO-VG32
Weight / Peso	150 g, 130 g (L)
Attachment / Accessori	L-type bracket (TU-BC2L) staffa a L (TU-BC2L)

ENCODING / CODIFICA

TU - L2 - 14 - □

<p>Model Modello</p>	<p>Port size: Connessione: 14 1/4"</p>	<p>Bowl /Tazza: L Longer Case Tazza lunga P Protection case Tazza protetta</p>
---------------------------------	---	---

DIMENSIONS / DIMENSIONI

